



ROLLER



PANEL



ROMAN

Technical Data

Composition	30% polyester / 70% PVC
Width	3,000mm
Weight	413gsm +/-10%
Thickness	0.72mm +/-5%
Opacity/Openness	Approx. 6%
Light Fastness	≥ 5 (Blue wool scale)
Coating	Polyester yarns with PVC coating
Flame Retardant	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings
Cleaning	Wipe clean with warm soapy water and damp cloth



5 YEAR
WARRANTY



SCREEN



ECO
FRIENDLY



FLAME
RETARDANT



FR



Solar Properties

USA Standard Tested To Ashrae 74-73

	Ts	Rs	As	Tv/Vlt	O-F	Shading Coefficients (Sc)		
						3mm CL.	6mm CL.	9mm CL.
Quartz	26	63	11	8	6	0.38	0.38	0.34
Marble	25	50	25	5	6	0.37	0.36	0.34
Ore	23	47	30	6	6	0.38	0.37	0.40
Granite	7	4	89	7	6	0.74	0.70	0.51
Flint	10	11	79	8	6	0.70	0.67	0.49
Coal	8	4	88	8	6	0.74	0.70	0.51

Ts Solar Transmittance

As Solar Absorbance

Tv Visual Light Transmission

G-Value % Solar Radiation through Fabric

Rs Solar Reflection

Tuv Ultraviolet Transmittance

O-F Openness Factor

G-Total % Solar Radiation through Blind and Window

Melbourne Head Office

Building 1, Level 2, 630 Mitcham Road
Mitcham VIC 3132 Australia

P +61 3 9729 9970
E sales@texstyle.com.au

Learn more at
texstyle.com.au

